

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 09-Sep-2009 Revision Date 11-Oct-2023 Revision Number 8

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

 Product Description:
 Sodium ethoxide, 21% in ethanol

 Cat No. :
 429300000; 429301000; 429308000

Molecular Formula C2 H5 Na O

Unique Formula Identifier (UFI) YU9Q-XTQN-DW02-UQ2T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services

Ireland: National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 3 (H226)

Sodium ethoxide, 21% in ethanol

Revision Date 11-Oct-2023

Health hazards

Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Category 1 B (H314) Category 1 (H318)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

EUH014 - Reacts violently with water

Precautionary Statements

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Ethyl alcohol	64-17-5	200-578-6	79	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)
Sodium ethoxide	141-52-6	EEC No. 205-487-5	21	Flam. Sol. 1 (H228) Self-heat. 1 (H251) Skin Corr. 1B (H314) Eye Dam. 1 (H318)

Sodium ethoxide, 21% in ethanol

Revision Date 11-Oct-2023

		EUH014

	Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Ī	Ethyl alcohol	Eye Irrit. 2 :: C>=50%	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required. Keep eye wide open while rinsing.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean

mouth with water. Call a physician immediately.

Inhalation If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or

inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove from exposure, lie

down. Call a physician immediately.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water. Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Sodium ethoxide, 21% in ethanol

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Thermal decomposition can lead to release of irritating gases and vapors.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe mist/vapors/spray. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from water or moist air. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

ACR42930

Revision Date 11-Oct-2023

Sodium ethoxide, 21% in ethanol

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Ethyl alcohol	TWA: 1000 ppm TWA; 1920		STEL: 1000 ppm 15 min
	mg/m³ TWA		
	WEL - STEL: 3000 ppm		
	STEL; 5760 mg/m ³ STEL		

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Ethyl alcohol		DNEL = 87 mg/kg bw/d		
64-17-5 (79)				

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol				DNEL = 343mg/kg
64-17-5 (79)				bw/day

Com	ponent	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
,	alcohol 7-5 (79)	DNEL = 1900mg/m ³			DNEL = 950mg/m ³
	n ethoxide 2-6 (21)	DNEL = 1mg/m ³	DNEL = 1 mg/m³, 0.1 mg/kg bw/day	DNEL = 1mg/m ³	DNEL = 1mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Sodium ethoxide	PNEC = 0.96mg/L	PNEC = 3.6mg/kg	PNEC = 2.75mg/L	PNEC = 580mg/L	PNEC = 0.63 mg/kg
141-52-6 (21)		sediment dw			soil dw

Comp	onent	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Sodium 6 141-52-		PNEC = 0.79mg/L			PNEC = 0.72g/kg food	

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use

A OD 10000

Revision Date 11-Oct-2023

Sodium ethoxide, 21% in ethanol

Revision Date 11-Oct-2023

explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas, Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure Small scale/Laboratory use

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Dark yellow **Appearance** Odor Alcohol-like **Odor Threshold** No data available Melting Point/Range No data available **Softening Point** No data available 91 °C / 195.8 °F **Boiling Point/Range** Flammability (liquid) Highly flammable

On basis of test data Liquid

Not applicable Flammability (solid,gas)

Explosion Limits Lower 3.5 vol% Upper 28 vol%

Flash Point 25 °C / 77 °F Method - No information available

Autoignition Temperature 425 - °C / 797 - °F

Sodium ethoxide, 21% in ethanol Revision Date 11-Oct-2023

Decomposition Temperature No data available

pH 13 @ 20°C 20 g/l aq. sol

Viscosity 23 Pa.s at 20 °C

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowEthyl alcohol-0.32

Vapor Pressure 38 hPa @ 20 °C

Density / Specific Gravity 0.868

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C2 H5 Na O Molecular Weight 68.04

Explosive Properties Vapors may form explosive mixtures with air explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity Yes

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing. Reacts violently with water.

10.4. Conditions to avoid

Incompatible products. Excess heat. Exposure to moist air or water. Exposure to moisture.

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release

of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information No acute toxicity information is available for this product

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met

DermalNo data availableInhalationNo data available

Toxicology data for the components

Sodium ethoxide, 21% in ethanol

Revision Date 11-Oct-2023

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg	-	LC50 = 117-125 mg/l (4h)
	OECD 401 (Rat)		OECD 403 (rat)
	3450 mg/kg (Mouse)		20000 ppm/10H (rat)

Category 1 B (b) skin corrosion/irritation;

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

Component	Test method	Test species	Study result
	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
64-17-5 (79)		mouse	non-sensitising
	OECD Test Guideline 429		· ·
	Local Lymph Node Assay		

No data available (e) germ cell mutagenicity;

Component	Test method	Test species	Study result
Ethyl alcohol	AMES test	in vitro	negative
64-17-5 (79)	OECD Test Guideline 471	Bacteria	_
	Gene cell mutation		
	OECD Test Guideline 476	in vitro	negative
		Mammalian	_

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

No data available (a) reproductive toxicity:

Component	Test method	Test species / Duration	Study result
Ethyl alcohol 64-17-5 (79)	OECD Test Guideline 416	Oral / mouse 2 Generation	NOAEL = 13.8 g/kg/day
04-17-3 (79)	OECD Test Guideline 414	2 Generation	
		Inhalation / Rat	NOAEC = 16000 ppm

Reproductive Effects Adverse reproductive effects have occurred in humans. **Developmental Effects** Substances known to cause developmental toxicity in humans.

(h) STOT-single exposure; No data available

No data available (i) STOT-repeated exposure;

No information available. **Target Organs**

(j) aspiration hazard; No data available

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and

Sodium ethoxide, 21% in ethanol

Revision Date 11-Oct-2023

danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

	Component	Freshwater Fish	Water Flea	Freshwater Algae
I	Ethyl alcohol	Fathead minnow (Pimephales	EC50 = 9268 mg/L/48h	EC50 (72h) = 275 mg/l (Chlorella
		promelas) LC50 = 14200	EC50 = 10800 mg/L/24h	vulgaris)
-		mg/l/96h		

Component	Microtox	M-Factor
Ethyl alcohol	Photobacterium phosphoreum:EC50 = 34634	
	mg/L/30 min	
	Photobacterium phosphoreum:EC50 = 35470	
	mg/L/5 min	

12.2. Persistence and degradability

Persistence

Soluble in water, Persistence is unlikely, based on information available, Miscible with water.

Component	Degradability
Ethyl alcohol	OECD 301E = 94%
64-17-5 (79)	

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems . Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

Revision Date 11-Oct-2023 Sodium ethoxide, 21% in ethanol

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

> application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Solutions with high pH-value must be neutralized before

discharge.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN2924

14.2. UN proper shipping name FLAMMABLE LIQUID, CORROSIVE, N.O.S.

Technical Shipping Name Ethyl alcohol, Sodium ethoxide

14.3. Transport hazard class(es) **Subsidiary Hazard Class** 8 14.4. Packing group П

ADR

14.1. UN number UN2924

FLAMMABLE LIQUID, CORROSIVE, N.O.S. 14.2. UN proper shipping name

Technical Shipping Name Ethyl alcohol, Sodium ethoxide

14.3. Transport hazard class(es) 3

Subsidiary Hazard Class 8 14.4. Packing group II

IATA

14.1. UN number UN2924

14.2. UN proper shipping name FLAMMABLE LIQUID, CORROSIVE, N.O.S.

Technical Shipping Name Ethyl alcohol, Sodium ethoxide

14.3. Transport hazard class(es) 3 **Subsidiary Hazard Class** 8 II 14.4. Packing group

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

Not applicable, packaged goods 14.7. Maritime transport in bulk according to IMO instruments

SECTION 15: REGULATORY INFORMATION

Revision Date 11-Oct-2023

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	ı	-	X	X	KE-13217	Χ	X
Sodium ethoxide	141-52-6	205-487-5	-	-	Х	X	X	Χ	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	Х	Х
Sodium ethoxide	141-52-6	X	ACTIVE	Х	-	X	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Sodium ethoxide	141-52-6	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Sodium ethoxide	141-52-6	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

Sodium ethoxide, 21% in ethanol

Revision Date 11-Oct-2023

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl alcohol	WGK1	
Sodium ethoxide	WGK 1	

Component	France - INRS (Tables of occupational diseases)	
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84	

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 (79)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

H225 - Highly flammable liquid and vapor

H251 - Self-heating; may catch fire

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

EUH014 - Reacts violently with water

H228 - Flammable solid

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

IARC - International Agency for Research on Cancer

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists **DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

EC50 - Effective Concentration 50%

TWA - Time Weighted Average

LD50 - Lethal Dose 50%

POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

Predicted No Effect Concentration (PNEC)

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

MARPOL - International Convention for the Prevention of Pollution from

Ships ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Sodium ethoxide, 21% in ethanol Revision Date 11-Oct-2023

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data
Health Hazards Calculation method
Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Creation Date09-Sep-2009Revision Date11-Oct-2023Revision SummaryNot applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet