

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	<u>3-Methyl-1-butanol</u>
Cat No. :	36716
Synonyms	Isoamyl alcohol; Isopentyl alcohol
CAS No	123-51-3
EC No	204-633-5
Molecular Formula	C5 H12 O
REACH registration number	-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company	Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific) Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608
----------------	--

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids

Category 3 (H226)

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Health hazards

Acute Inhalation Toxicity - Vapors
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 4 (H332)
Category 2 (H315)
Category 2 (H319)
Category 3 (H335)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Warning

Hazard Statements

H226 - Flammable liquid and vapor
H332 - Harmful if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P337 + P313 - If eye irritation persists: Get medical advice/attention
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and
-----------	--------	-------	----------	---

ALFAA36716

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Isoamyl alcohol	123-51-3	EEC No. 204-633-5	<=100	UK SI 2020/1567 Flam Liq. 3 (H226) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) (EUH066)
-----------------	----------	-------------------	-------	--

REACH registration number	-
----------------------------------	---

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
Ingestion	Do NOT induce vomiting. Get medical attention.
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention. If not breathing, give artificial respiration.
Self-Protection of the First Aider	Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors.

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Use only non-sparking tools.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALFAA36716

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Isoamyl alcohol	STEL: 125 ppm 15 min STEL: 458 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 366 mg/m ³ 8 hr		TWA: 5 ppm 8 hr. TWA: 18 mg/m ³ 8 hr. STEL: 10 mg/m ³ 15 min STEL: 37 ppm 15 min

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Isoamyl alcohol 123-51-3 (<=100)	DNEL = 292mg/m ³		DNEL = 73.16mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Isoamyl alcohol 123-51-3 (<=100)	PNEC = 0.12mg/L	PNEC = 0.496mg/kg sediment dw	PNEC = 1.2mg/L	PNEC = 37mg/L	PNEC = 0.0287mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Isoamyl alcohol 123-51-3 (<=100)	PNEC = 0.012mg/L	PNEC = 0.0496mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Clear	
Odor	Characteristic	
Odor Threshold	No data available	
Melting Point/Range	-117 °C / -178.6 °F	
Softening Point	No data available	
Boiling Point/Range	130 - 132 °C / 266 - 269.6 °F	760 mm HG
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.0 Vol% Upper 8 Vol%	
Flash Point	45 °C / 113 °F	Method - No information available
Autoignition Temperature	365 - °C / 689 - °F	
Decomposition Temperature	335 °C	
pH	6.5	25 g/l aq.sol
Viscosity	4.3 mPa s at 20 °C	
Water Solubility	25 g/L (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Isoamyl alcohol	1.35	
Vapor Pressure	4 hPa @ 20 °C	
Density / Specific Gravity	0.807-0.811	
Bulk Density	Not applicable	Liquid
Vapor Density	3.04 (Air = 1.0)	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Molecular Formula C5 H12 O
Molecular Weight 88.15
Explosive Properties explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials Strong oxidizing agents. Metals. Alkali metals. Halogens. Acids. Acid anhydrides. Acid chlorides. Isocyanates.

10.6. Hazardous decomposition products Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isoamyl alcohol	LD50 = 5770 mg/kg (Rat)	LD50 = 3250 mg/kg (Rabbit)	LC50 > 2000 ppm (Rat) 8 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;
Respiratory Based on available data, the classification criteria are not met
Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

(f) **carcinogenicity;** Based on available data, the classification criteria are not met
There are no known carcinogenic chemicals in this product

(g) **reproductive toxicity;** Based on available data, the classification criteria are not met

(h) **STOT-single exposure;** Category 3
Results / Target organs Respiratory system.

(i) **STOT-repeated exposure;** Based on available data, the classification criteria are not met
Target Organs None known.

(j) **aspiration hazard;** Based on available data, the classification criteria are not met
Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects This product contains the following substance(s) which are hazardous for the environment. .

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isoamyl alcohol	LC50 96 h 700 mg/L (rainbow trout)	EC50: = 260 mg/L, 48h (Daphnia magna)	EC50: = 181 mg/L, 96h (Desmodesmus subspicatus) EC50: = 493 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Isoamyl alcohol	EC50 = 2500 mg/L 17 h	

12.2. Persistence and degradability Readily biodegradable
Persistence Soluble in water, Persistence is unlikely, based on information available.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Isoamyl alcohol	1.35	No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

assessment and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant This product does not contain any known or suspected substance

Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1105
14.2. UN proper shipping name PENTANOLS
14.3. Transport hazard class(es) 3
14.4. Packing group III

ADR

14.1. UN number UN1105
14.2. UN proper shipping name PENTANOLS
14.3. Transport hazard class(es) 3
14.4. Packing group III

IATA

14.1. UN number UN1105
14.2. UN proper shipping name PENTANOLS
14.3. Transport hazard class(es) 3
14.4. Packing group III

14.5. Environmental hazards No hazards identified

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Isoamyl alcohol	123-51-3	204-633-5	-	-	X	X	KE-23575	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Isoamyl alcohol	123-51-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isoamyl alcohol	123-51-3	-	-	-

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Isoamyl alcohol	123-51-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Isoamyl alcohol	WGK1	
-----------------	------	--

Component	France - INRS (Tables of occupational diseases)
Isoamyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor
H332 - Harmful if inhaled
H315 - Causes skin irritation
H335 - May cause respiratory irritation
EUH066 - Repeated exposure may cause skin dryness or cracking
H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

SAFETY DATA SHEET

3-Methyl-1-butanol

Revision Date 09-Feb-2024

Prepared By Health, Safety and Environmental Department
Creation Date 13-Sep-2010
Revision Date 09-Feb-2024
Revision Summary New emergency telephone response service provider.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet